

Amendments to the Claims

This listing of claims will replace all prior versions and listings of claims in the application:

Listing of Claims:

Claims 1 – 21 (cancelled)

Claim 22 (currently amended): A method which may be used for cooling a stream of gaseous fluid comprising:

- a) ~~confining said~~ introducing a confined stream of said gaseous fluid into a chamber;
- b) slowing the flow rate of said fluid by increasing the cross section of said stream, ~~wherein said flow rate of said fluid is slowed by directing said stream toward an impact surface;~~
- c) spraying liquid nitrogen into said stream to cool said fluid, wherein said steps of slowing and spraying are performed within said chamber; and
- d) diverting at least a portion of the cooled fluid and allowing said diverted portion to exiting exit said confinement.

Claim 23 (currently amended): The method of claim 22, ~~further comprising~~ wherein said step of diverting said portion of said fluid only after said liquid nitrogen has completely vaporized in said stream.

Claim 24 (previously presented): The method of claim 22, wherein said stream is cooled rapidly.

Claim 25 (previously presented): The method of claim 22, wherein said cooling process begins with substantially little start up time.

Claim 26 (cancelled)

Claim 27 (previously amended): The method of claim 22, further comprising stirring said stream after said spraying and before said diversion.

Claim 28 (previously presented): The method of claim 27, further comprising stirring said stream with a turbomachine means.

Claim 29 (previously presented): The method of claim 27, further comprising stirring said stream by deflection.

Claim 30 (previously presented): The method of claim 22, further comprising regulating the temperature of said recovered fluid by adjusting the flow rate of said liquid nitrogen.

Claim 31 (previously amended): The method of claim 22, wherein the temperature of said diverted fluid is about -150°C to about -196°C .

Claim 32 (currently amended): A method ~~which may be used to cool~~ for cooling objects comprising:

- a) cooling a stream of gaseous fluid, wherein said cooling further comprises:
 - 1) confining said stream;
 - 2) slowing the flow rate of said fluid by increasing the cross section of said stream, ~~wherein said flow rate of said fluid is slowed by directing said stream toward an impact surface;~~
 - 3) spraying liquid nitrogen into said stream to cool said fluid; and
 - 4) diverting at least a portion of the cooled fluid and allowing said diverted portion to exit ~~exiting~~ said confinement; and
- b) applying said diverted portion of said fluid directly to said objects thereby cooling them.

Claim 33 (previously presented): The method of claim 32, wherein said objects comprise foodstuffs.

Claim 34 (previously presented): The method of claim 33, wherein said foodstuffs comprise chocolate.

Claim 35 (previously amended): The method of claim 32, further comprising diverting said portion of said fluid only after said liquid nitrogen has completely vaporized in said stream.

Claim 36 (cancelled)

Claim 37 (previously presented): The method of claim 32, wherein said gaseous fluid comprises air.

Claim 38 (previously amended): The method of claim 32, wherein the temperature of said diverted fluid is about -150°C to about -196°C .

Claim 39 (currently amended): An apparatus which may be used for cooling a stream of gaseous fluid comprising:

- a) a mixing pipe through which said stream passes;
- b) at least one impact surface located inside said mixing pipe;
- c) a means for spraying liquid nitrogen into said mixing pipe, and
- d) an injection pipe for injecting said fluid into said mixing pipe, wherein said mixing pipe has a cross-section larger than that of ~~impact surface and said spraying means~~ said injection pipe.

Claim 40 (previously presented): The apparatus of claim 39, wherein said spraying means further comprises a spray nozzle which discharges into said mixing pipe in substantially the fluid flow direction.

Claim 41 (previously presented): The apparatus of claim 39, wherein said injection pipe is located in the upstream end of said mixing pipe.

Claim 42 (previously presented): The apparatus of claim 39, wherein said impact surface substantially faces the upstream end of said mixing pipe.

Claim 43 (previously presented): The apparatus of claims 39, wherein said impact surface is concave.

Claim 44 (previously presented): The apparatus of claim 39, further comprising a means for stirring said gaseous fluid, said stirring means located downstream of said spraying means.

Claim 45 (cancelled)

Claim 46 (previously presented): The apparatus of claim 44, further comprising:

- a) a chamber into which the downstream end of said mixing pipe discharges;
- b) a calming passage for said gaseous fluid defined by said chamber and said pipe; and
- c) a chamber exit for said fluid located at substantially the same level as said calming passage.

Claim 47 (previously presented): The apparatus of claim 46, wherein said stirring means is located upstream of said calming passage.

Claim 48 (previously presented): The apparatus of claim 46, wherein the upstream end of said mixing pipe is open and located in said chamber.

Claim 49 (previously presented): The apparatus of claim 46, further comprising a suction means located downstream of said spraying means and upstream of said exit, wherein said suction means is able to drive said gaseous fluid in said flow direction.

Claim 50 (previously presented): The apparatus of claim 49, wherein a turbomachine is common to said stirring means and said suction means.

Claim 51 (previously presented): The apparatus of claim 50, wherein said turbomachine comprises a centrifugal fan located at the downstream end of said mixing pipe, wherein said fan is able to draw in said gaseous fluid flowing in said mixing pipe.

Claim 52 (currently amended): An apparatus which may be used for cooling a stream of gaseous fluid comprising:

- a) a mixing pipe through which said stream passes;
- b) at least one impact surface located inside said mixing pipe;
- c) a means for spraying liquid nitrogen into said mixing pipe, and
- d) an injection pipe for injecting said fluid into said mixing pipe, wherein said mixing pipe has a cross-section larger than that of impact surface and said spraying means, and
- e) a regulation loop for regulating the outlet temperature of said gaseous fluid leaving said cooling device to a preset temperature, said regulation loop comprising:
 - i) a means for measuring said outlet temperature;
 - ii) a means for adjusting the flow rate of nitrogen supplied to said spraying means, and
 - iii) an actuator, wherein said actuator receives a signal from said measuring means and actuates said adjusting means.

Claim 53 (currently amended): An apparatus which may be used for cooling ~~foodstuffs~~ articles with a stream of gaseous fluid comprising:

- a) a mixing pipe through which said stream passes;
- b) at least one impact surface located inside said mixing pipe; and
- c) a means for spraying liquid nitrogen into said mixing pipe; and
- d) an injection pipe for injecting said ~~foodstuffs~~ gaseous fluid into said mixing pipe, wherein said mixing pipe has a cross-section larger than that of ~~impact surface and said spraying means~~ said injection pipe.

Claim 54 (cancelled)